

Surface Conditioner 56170

DESCRIPTION

A quality penetrating primer spray applied to a concrete substrate. Complies with CGSB. 37-GP-9M.

BASIC USE

For priming and sealing concrete substrate to improve the bond of MM6125EV. Use for priming concrete, masonry and similar surfaces.



TECHNICAL DATA

COLOR	Black
SOLID	37% (approx.)
WEIGHT PER LITRE	0.867 kg/l
COVERAGE	1-2 litres per 10 sq m (300-600 sq ft/gallon)
DRYING TIME	to 20°C, 50% humidity, 2 hours- touch dry
SERVICE TEMPERATURE	-30°C @ 85°C (-22°F @ 185°F)
FLAMMABILITY	Combustible

INSTALLATION

Apply by brush, roller or spray. Allow to dry before applying membrane, usually 2-3 hours.

LIMITATIONS

Solvent in product attacks polystyrene insulation. Avoid use where solvent odours may be exposed to food or other susceptible products.

PREPARATION

Surface must be dry and free from dust, dirt, grease and other foreign matter.

LEED INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Montreal, Quebec, Canada
Extraction/Harvesting Location		Asphalt: Toronto
VOC Content (g/litre)		370

The contents and methods described herein are the intellectual property of Hydrotech Membrane Corp.. The information is based on data and knowledge considered to be true and correct at the time of publication and is offered for the user's consideration, investigation and verification. The information is subject to change without notice. The determination of suitability and fitness of the products and the application described herein for a particular purpose are the sole responsibility of the user. Please read all statements, recommendations and suggestions in conjunction with the conditions of sale which apply to all goods sold by Hydrotech Membrane Corp., including the express disclaimers by each company of the implied warranties of merchantability or fitness for a particular purpose.